



Protective Lining To IPS Diaphragm Wall BMA Waste Water Project Phase 1- Din Daeng

The aggressive atmospheric conditions expected in the Inlet Pumping Station required the application of a highly dense and compacted cementitious lining system to protect the diaphragm wall concrete.

A fiber reinforced base coat and specialist SO₂ protective top coat were proposed and applied by Hammersmith from specially designed climbing platforms .

With three Reed gunite machines and a full compliment of ancillary equipment at its disposal, Hammersmith was able to respond quickly and efficiently to the clients needs.



**“SPECIALIST SOLUTIONS
FOR THE
CONSTRUCTION INDUSTRY”**

HAMMERSMITH LIMITED

38/1 Soi Naphasap Yak 1 Sukhumvit Soi 36,
Klongtoey, Bangkok 10110 THAILAND
Phone: (662) 661 5962/3
Fax: (662) 661 5986
Email: email@hammersmithgroup.com
Web: www.hammersmithgroup.com

PROJECT DETAILS

Project Title	BMA Waste Water Project Phase I – Din Daeng Inlet Pumping Station Sulfur Dioxide protective lining
Client	NOSS Consortium
Project Details	2,500 m ² of “Calcote” (calcium aluminate based cement) modified gunite protection to the IPS D-wall
Duration	Two months
Equipment	Reed “SOVA” and “LOVA” pneumatic Guncrete machines
Completion Date	September, 1996